

# Covert Camera

## PIR Camera / Smoke Detector Camera / Sprinkler Camera HS-CH0120/HS-CH0121/HS-CH0130/HS-CH0131

HS-CH0120  
HS-CH0121






HS-CH0130



HS-CH0131



### Dimension Unit : mm



HS-CH0120  
HS-CH0121

- Covert PIR / smoke / sprinkler type camera.
- Built-in Lens 3.7mm / F2.0.
- DC12V voltage.
- Audio Microphone(HS-CH0121).

### Specifications

Model	HS-CH0120	HS-CH0121	HS-CH0130	HS-CH0131
Pick up device	1/3" SONY Super HAD CCD			
Total Pixels	NTSC:811(H)x508(V)/PAL:795(H)x596(V)			
Effective Pixels	NTSC:768(H)x494(V)/PAL:752(H)x582(V)			
Resolution	600TV lines			
Synchronization	Internal			
Scanning System	2:1 Interlace			
Electronic Shutter	NTSC:1/60~1/100,000, PAL:1/50~1/110,000			
Min. Illumination	0.26 Lux / F2.0			
S/N Ratio	More than 48dB			
White Balance	Auto			
AGC	Auto			
Video Output	1 Vp-p / 75 Ohms			
Audio Microphone	N/A	Yes		N/A
Power Source	DC12V±10%			
Power Consumption	96mA	100mA		96mA
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)			
Dimension	70(W) x 120(H) x 75.9(D)mm		56.5(H) x 120(Diameter)mm	95(H) x 84(Diameter)mm

### Dimension Unit : mm

