


Intercom unit



SIP addressable digital intercom unit

50.30.0010 per piece

- › Digital audio intercom unit for communication with the residents or patients.
 - Allows nurses to assess the call
 - Allows nurses to check up on patients remotely
 - Gives peace of mind to the residents or patient by knowing they are being heard.
- › The intercom unit connects to the AQURA ward controller over the audio link.
- › Intercom units are SIP addressable
- › Hands free communication up to 5 meter
- › Echo cancellation and noise suppression for clear speech intelligibility
- › Auto pickup preceded by a tone when a nurse call is active.
- › An integrated privacy LED indicates a conversation is ongoing.
- › Magnetic sensor for servicing
- › Modular unit to be mounted on a mounting frame (not included)

Specifications:

| | |
|---------------------------|--|
| Dimensions (LxWxH) | 91 x 91 x 21 mm |
| Material | PC/PBT - UV stabilized - V-0 flame retardant Main color: RAL9016 |
| IP rating | IP40 |
| Power input | 24VDC ± 10% Protected by self resetting fuse Protected against reverse polarity |
| Power consumption | Device standby current: 64 mA Device maximum current: 150 mA |
| Connectivity | AQURA audio link |
| Regulation | CE, RoHS |
| Mounting | Requires an AQURA frame to be mounted on (see accessories) Can be mounted on a wall box with an AQURA mounting frame. Can be mounted on a surface with an AQURA surface mounting frame. |
| Connectors | 2x 50.08.1015 (audio link) - not included Power connector 50.08.1212. |

Unit accessories:

| | | |
|--|---|-------------------|
| | Single mounting frame for units per 10 | 50.09.1010 |
| | Double mounting frame for units per 10 | 50.09.1020 |
| | Single surface mounting frame 30mm for units - per 10 | 50.09.1210 |
| | Screw connectors 5 positions pack of 50 | 50.08.1015 |
| | Power terminal block 2 positions pack of 50 | 50.08.1212 |