

SERIES 1390

Surface mounting electromagnet door holders


- Surface mounting
- Holding force 150 300 500 kg
- Damping counterplate included
- 12-24V DC power supply
- IP 40 and IP 65 protection
- UL approval

Series of surface mounting electromagnet door holder to block emergency, anti-panic, access and passage doors. The high holding force allows to keep doors closed under normal condition. In case of emergency, electromagnet unit is released, allowing door opening. Fail safe operation: the door is released in case of power drop, enabling the safe passage of people. Outdoor version available. 12 or 24VDC power supply, selectable through internal jumper. Thanks to wide range of auxiliary brackets, they can be mounted in several applications including glazed doors. These doors holder unit can be released by emergency button or specific control panel.

GENERAL SPECIFICATIONS

Housing material	Annealed aluminium				
Magnetic part	Galvanized steel				
Operation	Release without power supply				
Connection type	Terminal				
Operating temperature	-10°C to + 55°C				
Standard equipment	Galvanized steel counterplate,				
	screws and mounting accessories				
Packaging	1 pcs. / package				

	Α	В	С
1384 A	170	35	21
1388 A	250	48	25
1390 A	265	70	40



ORDER CODES

Code	Holding force ±15 %	Power supply	Nominal current	Door status	Mounting	IP degree	Package weight	Notes
1384 A	150 kg / 1470 N	12-24V DC	300 mA @ 12V DC 150 mA @ 24V DC	yes	Surface mounting	IP 40	1,80 kg	
1388 A	300 kg / 2490 N	12-24V DC	500 mA @ 12V DC 250 mA @ 24V DC	yes	Surface mounting	IP 40	2,02 kg	
1392 A	500 kg / 4900 N	12-24V DC	500 mA @ 12V DC 250 mA @ 24V DC	yes	Surface mounting	IP 40	4,26 kg	
1394 A	2 x 300 kg 5890 N	12-24V DC	1 A @ 12V DC 500 mA @ 24V DC	yes	Surface mounting	IP 40	4 kg	N° 2 counterplates included
1395 A	2 x 500 kg 9800 N	12-24V DC	1 A @ 12V DC 500 mA @ 24V DC	yes	Surface mounting	IP 40	8,60 kg	N° 2 counterplates included
1396 A	500 kg / 4900 N	12-24V DC	500 mA @ 12V DC 250 mA @ 24V DC	no	Surface mounting	IP 65	4,20 kg	Stainless steel, outdoor use, wire connection

1396 A



