

# ATS1235

## 16-32 zones Gen2 868AM wireless receiver including plastic housing

### Product Overview

The ATS1235 Advanced Wireless Data Gathering Panel (DGP) receiver expands the Advisor Advanced & Master panel's input capability respectively by up to 32 zones using UTC F&S 868MHz Gen 2 Wireless Sensors: i.e. PIR, Glassbreak etc. Maximum distance from the panel is 1500 meters.

The ATS1235 features spatial diversity to minimize wireless signal nulls or dead spots and has a nominal open-air receiving range of 400m. If dead spots need to be eliminated, a 868MHz repeater may be used. It may be powered from the Advisor Master BUS power or a remote auxiliary power supply.

Fob buttons may be programmed for users to arm and disarm or to control relays.

With ATS1235 Advanced wireless DGPs, the ATS panel can be configured as a hybrid system where you can optimise the system by distributed receivers in the premises.

### Data Gathering Panels

Data Gathering Panels (DGP) are used to expand the number of alarm inputs on the system and allow inputs and relays to be connected at a location remote from the Advisor Advanced / MASTER panel. DGPs communicate via poll & reply messages and send alarms to the control panel for processing. The DGPs collect information from detectors, door contacts and other similar devices. There are DGPs available for conventional devices, wireless devices as well as for intelligent addressable devices. A special DGP is also available for collecting the information for either four doors or lifts.

### System databus connection

The system databus is used to connect Data Gathering Panels (to provide extra zones) and Arming Stations to the ATS control panel. Remote devices can be up to 1.5 km from an ATS control panels. Arming stations and Data Gathering Panels must be connected via a 2 pair twisted shielded data cable from the system databus connection. (WCAT 52 is recommended). The shield of the data cable should be connected to earth at the ATS control panel and should be left disconnected at any other end.

### Functionality

The ATS1235 Wireless Data Gathering Panel (DGP) receiver expands the Advisor Master panel's input capability by up to 32 zones and the ATS Advanced by 16 zones using UTC F&S "Learn Mode" 868MHz Wireless Transmitter.

The ATS1235 may be located up to 1500 meters from the ATS Control panel using a WCAT52/54 cable.

Fob buttons may be programmed for users to arm and disarm or to control relays, for example, to remotely open and close a garage door



### Details

- Expands the Advisor Advanced panel with 32 wireless zones
- Expands the ATS Master panel's input capability by up to 32 wireless zones
- Using the UTC Security "Learn Mode" 868MHz Wireless Transmitter Sensors (crystal or SAW)
- May be located up to 1500 meters from the Advisor Master panel using WCAT52/54 cable.
- Features spatial diversity to minimize wireless signal nulls or dead spots and has a nominal open-air receiving range of 460m
- If dead spots need to be eliminated a UTC Fire & Security 868MHz repeater may be used
- Powered from the panel BUS power or a remote auxiliary power supply
- Fob buttons may be programmed for users to arm and disarm or to control relays
- To remotely open and close a garage door as well as arm or disarm an office security system

as well as arm or disarm an office security system.

## **EN50131**

---

The ATS1235 meets prEN50131-5-3:2004 Grade 2 specifications for wireless systems like Detector supervision and local and remote attenuation of - 6dB for commissioning and maintenance.

# ATS1235

## 16-32 zones Gen2 868AM wireless receiver including plastic housing

### Technical specifications

---

#### General

Expander type	Wireless expander
Product line	Advisor Advanced, ATS Master
Connection type	Databus connection
Compatibility	868MHz Gen2 sensors, ATS Advanced FW v017.017.0067 or higher, ATS Master FW v04.09.16 or higher
Max. distance from panel	1.5 km
Max. per panel	15 / 30 (depending on panel type)
Specified cable	WCAT52/54

#### System

Addressing	DIP Switches
------------	--------------

#### Inputs

No. of wireless zones	32 (16 wireless keyfobs)
-----------------------	--------------------------

#### Wireless

Operating frequency	868 MHz AM
Wireless open-air range	400 m

#### Electrical

Operating voltage	9.5 to 14.4 VDC
Current consumption	70 mA $\pm$ 10%
Integrated power supply	No

#### Physical

Physical dimensions	165 x 115 x 40 mm
Net weight	350 g
Housing	TX-9000-03-1

#### Environmental

Operating temperature	-10°C to +55°C
Relative humidity	95% noncondensing
Environment	EN50130-5 ; Class II - Indoor (General)

#### Standards & regulation

Certification	EN50131 Grade 2
---------------	-----------------

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 8 May 2020 - 16:48

